

LX Wick

LX wick features a special flat braided coreless wick that curls throughout the burn cycle. This unique feature minimizes carbon buildup and reduces smoking since the curl moves to the flame's highest heat concentration area. Added benefits of the curl are a tighter, more controlled flame profile and a self-trimming effect. Also, this wick series is lead and zinc-free.

Features:

- ❖ Special flat braided coreless wick that curls throughout the burn cycle.
- ❖ Designed to be used in votives, pillars, and containers.
- ❖ Lead and zinc-free.

Wick Designation	Yield (yds/lb)	ROC (oz/hr)	Flame Height (inches)	Pool Diameter (inches)
LX 8	853	0.13	1.1	2
LX 10	774	0.15	1.1	2
LX 12	646	0.18	1.2	2.1
LX 14	548	0.19	1.3	2.1
LX 16	481	0.2	1.4	2.2
LX 18	441	0.2	1.5	2.2
LX 20	402	0.22	1.5	2.3
LX 21	352	0.25	1.7	2.6
LX 22	325	0.27	1.8	2.8
LX 24 NST 2	296	0.3	2	3.1
LX 26 NST 2	276	0.32	2.2	3.3
LX 28 NST 2	253	0.34	2.4	3.5
LX 30 NST 2	238	0.36	2.5	3.7

Disclaimer

The rate charts provided in this document are meant to serve only as a guide for our customers to assist them in wick selection. Many variables exist in candle wax types, additives and formulations for individual candle systems. Final wick selection should always be confirmed through the customer's own testing process to determine if a particular wick is the correct choice for a particular candle system. Wicks Unlimited is not responsible for selections made by the customer using any of the reference material contained in this catalog. For optimal burn performance in specific candle systems, we strongly recommend that customers conduct exhaustive burn tests in their own burn lab and consider retaining samples for their future internal reference. The importance of candle testing and data validation cannot be overstated.

For more information on testing and standards, visit www.wicksunlimited.com



ASTM INTERNATIONAL

