



## Ply™ Wick

Often referred to as flat, classic, or regular wick, Ply™ wick is a popular option for dipped, poured, or extruded candles. This wick is constructed of 100% natural fibers and curls at the tip throughout the combustion cycle reducing carbon buildup during its lifespan for an even burn.

### Features:

- ❖ Constructed with 100% natural fibers.
- ❖ Designed for use in tapers and pillars.
- ❖ Engineered to provide a slight curl when burned to reduce carbon buildup and allow an even burn.

Wick Designation	Yield (yds/lb)	ROC (oz/hr)	Flame Height (inches)	Pool Diameter (inches)
9 PLY	1565	0.1	0.81	1.59
12 PLY	1013	0.13	0.99	1.69
15 PLY	793	0.17	1.3	1.86
18 PLY	663	0.19	1.42	1.93
21 PLY	560	0.19	1.43	1.94
24 PLY	481	0.2	1.49	1.97
27 PLY	403	0.2	1.49	1.97
30 PLY	372	0.21	1.55	2
36 PLY	288	0.24	1.74	2.11
39 PLY	301	0.24	1.74	2.11
42 PLY	261	0.24	1.74	2.11
45 PLY	233	0.25	1.85	2.17
48 PLY	225	0.25	1.85	2.17
60 PLY	171	0.26	1.93	2.22

### Disclaimer

The rate charts provided in this document are meant to serve only as a guide for our customers to assist them in wick selection. Many variables exist in candle wax types, additives and formulations for individual candle systems. Final wick selection should always be confirmed through the customer's own testing process to determine if a particular wick is the correct choice for a particular candle system. Wicks Unlimited is not responsible for selections made by the customer using any of the reference material contained in this catalog. For optimal burn performance in specific candle systems, we strongly recommend that customers conduct exhaustive burn tests in their own burn lab and consider retaining samples for their future internal reference. The importance of candle testing and data validation cannot be overstated.

Wicks Unlimited  
 10000 Wicks Road  
 Dallas, TX 75243



ASTM  
INTERNATIONAL

