



Wicks Unlimited your Global Leader
For All of Your Candle Combustion Needs

Sustainers with Puncture Crimping

Wicks Unlimited manufactures and supplies metal candle sustainers with the option of puncture crimping. This top-selling sustainer enables candle manufacturers to create tabbed wicks from waxed wick on reels that consume all the fuel (wax) at the candle's end of life. High-speed automated machinery creates a small piercing in the sustainer's wall to generate additional fuel (wax) flow, allowing the candle to consume all the fuel (wax) at the candle's end of life. Metal candle sustainers with puncture crimping are manufactured from the highest quality tin-coated steel. The thick tin coating inhibits corrosion often caused by the fragrance, dyes, and essential oils common in candles sold

Features:

- U.S.-based manufacturer & supplier of metal candle sustainers.
- Wicks Unlimited's best-selling metal sustainers with puncture crimping enable manufacturers to develop candles that consume all the fuel (wax) at the end of life.
- Precision machinery pierces the sustainer's wall to generate additional wax (fuel) flow, allowing the candle to consume all the wax (fuel) at the end of its life.
- Metal sustainers with puncture crimping are available with neck heights of 6.0 mm and include safety neck sustainers with neck heights of 10.0 mm, 13.0 mm, 13.2 mm, and 14.5 mm.
- Manufacturers can select base diameter(s) ranging from 14.5 mm to 20.00 mm.
- Wick insertion hole diameters range from 2.1 mm to 3.0 mm.
- Manufactured from the highest quality .010" (0.254 mm) thick tin-coated steel to inhibit corrosion caused by fragrance and essential oils.
- Wicks Unlimited's sustainers are accredited by the Quality Association for Candles and adhere to strict quality standards thanks to ISO: 9001:2015 certified quality management system and state-of-the-art equipment.



worldwide. Discover why candle manufacturers worldwide rely on Wicks Unlimited's diverse collection of wick products to meet their production requirements.

Non-Puncture Sustainer

Sustainer	Base Diameter	Overall Height	Hole Diameter
A3792	15.0 mm .590"	6.0 mm .236"	2.4 mm .094"
A3779	15.0 mm .590"	6.0 mm .236"	3.0 mm .118"
A3957	20.0 mm .788"	6.0 mm .236"	2.1 mm .083"
A3797	20.0 mm .788"	6.0 mm .236"	2.4 mm .094"
A3796	20.0 mm .788"	6.0 mm .236"	3.0 mm .118"
A3881	20.0 mm .788"	6.0 mm .236"	4.1 mm .160"
A3798	15.0 mm .590"	10.0 mm .394"	2.4 mm .094"
A3777	15.0 mm .590"	10.0 mm .394"	3.0 mm .118"
A3961	20.0 mm .788"	10.0 mm .394"	2.1 mm .083"
A3800	20.0 mm .788"	10.0 mm .394"	2.4 mm .094"
A3799	20.0 mm .788"	10.0 mm .394"	3.0 mm .118"
A3850	15.0 mm .590"	13.0 mm .510"	3.0 mm .118"
A3851	15.0 mm .590"	13.0 mm .510"	2.4 mm .094"
A2149	15.0 mm .590"	13.2 mm .520"	2.4 mm .094"
A3874	14.5 mm .565"	14.5 mm .571"	3.0 mm .118"



ISO 9001:2015 Certified QMS • RAL Quality Mark Certified



Waxed Wick on Reels | Wick Clip Assemblies | Sustainers | Technical Services

1515 SW 13th Ct • Pompano Beach, Florida, 33069 • Phone: (954) 946-3500

webstore.wicksunlimited.com sales@wicksunlimited.com [f](#) WicksUnlimited [in](#) WicksUnlimited